
InterFAX Connector by ACDI

Published 9/16/2024

Overview

InterFAX Connector application and license works with PaperCut MFs Scan to Fax API-based connection to provide more secure and advanced functionality.



Requirements


- InterFAX Admin Account
- PaperCut MF server for Windows (version 21.2 and above)
- MFD that provides Scan to Fax Functionality (<u>current list</u>)
- Advanced Fax Connector License for each MFD
- InterFAX Connector Packs to cover number of devices that will connect to InterFAX
- .net Runtime 6.0 installed on the PaperCut server

Compatible MFDS (as of 12/15/2023)

Konica Minolta (Open API4.0+), Toshiba V3+, Sharp OSA n2, Xerox, Canon MEAP, HP OXP, Ricoh SmartSDK

Install InterFAX connector by ACDI

- Download the InterFAX connector and write down the authorization license sent to you by ACDI.
- 2. Make sure you are logged into the PaperCut application server as an admin that can install applications.
- 3. Run the InterFAX connector installer.
- Installer will walk you through confirming that all prerequisites are met for the application and install any necessary components.
- 5. When install is complete PaperCut application service must be restarted to enable the InterFAX connector option within PaperCut.




Enable Advanced Scan to Fax actions

1. Navigate to Devices > External Device List.



- 2. Select the device you want to set up for Advanced Scan to Fax. The Device Details: <device name> page is displayed.
- 3. Scroll down to the **Integrated Scanning** section.



- 4. Click Allow Advanced Scan to Fax actions to appear on the device.
- 5. If you don't want the basic scan actions available on the MFD, click **Prevent Basic Scan to Fax actions from appearing on the device**.

Creating a Fax Connection in PaperCut

Step 1: Set up the scan actions


You can create any number of scan actions to meet your needs.

- Select Devices > Scan Actions. The Scan Actions page is displayed with a list of all available scan actions.
- 2. In the **Actions** menu, click **Create new**. The **Scan Action Details** page is displayed.




Delivery via InterFAX connector

- 1. Select **Devices > scan actions**.
- 2. In the Actions menu, click Create new. The Scan Action Details page is displayed.
- 3. In the **Destination** section, select click **Fax**.



- 4. Complete the following fields:
- 5. Fax provider—Select your fax provider
- 6. **Label**—Enter a name for the scan action (maximum 25 characters). This label is displayed to the user on the device.




- 7. Complete the **Fax settings** area with the Customer Name and Activation Key from Activation Email from ACDI, as well as the Username and Password of your InterFAX user.
- 8. If you use a PCI-compliant Interfax service, set the Endpoint to either PCI, PCI_US, or PCI_CA, depending on your Interfax settings.

| Fax settings | Fax server settings |
|---|---------------------------------|
| Fax server settings specify the parameters needed to connect to the fax provider. These settings can change depending on the selected fax provider. | Customer Name |
| | Access Control Devices, Inc. |
| | Activation Key |
| | jfRyah9Bas0LYgeoNEY5pCUIrKmk7LF |
| | Username |
| | admin |
| | Password |
| | ••••• |
| | Endpoint |
| | default v |


10. In the **How users select the recipient at the device** section:

9.

- 11. If you are setting up a fixed recipient, select **Fixed recipient** and complete the following fields:
 - **Fax number**—The fax number of the recipient.
 - **Recipient name**—The name of the recipient. This information will appear on the fax cover sheet, depending on your cover page configuration. Optionally, you can make this field non-editable.
 - **Recipient company name**—The company name of the recipient. This information will appear on the fax cover sheet, depending on your cover page configuration. Optionally, you can make this field non-editable.




• If you want to let the users enter the fax number at the MFD, select **Users can** specify the recipient.




Step 2: Configure the capture settings

1. Click **Options > Capture**. The Capture screen is displayed.



- In the **Document Processing** section, you can configure the optional **Despeckle** and **Deskew** settings. These settings apply to all new and existing scan actions:
 - Despeckle
 - Deskew
- 2. Select up to 10 languages you want OCR to detect and process in your scans.



3. Click Apply.

Step 3: Enable Integrated Scanning for a device

For each scanning device, you must enable Integrated Scanning.

- In the Admin web interface, click the **Devices** tab.
 The **External Device List** page is displayed.
- 2. Select a device.
 - The **Device Details** page is displayed.
- 3. In the Integrated Scanning area, select the Enable Integrated Scanning check box.
- 4. Click **OK**. For all scan actions except Scan to Fax, integrated scanning is now set up and you have finished the basic configuration.